



Mini Pocket MultiMeter



Autoranging with 8 functions

Including Battery Test and EF (Electric Field) Test

Features:

- Large 4000 count high contrast LCD display with bargraph
- Auto Power off to conserve battery life
- Autoranging with Data Hold and Range Hold
- EF Test (Electrid Field), Battery Check, Diode Test and Continuity Beeper
- Built-in storage compartment for integrated test leads
- Over-range and low battery indication
- Designed to IEC1010, CAT II 400V
- Complete with test leads and two LR44 button batteries

Applications:

- Tilt display adjusts 0° to 80° for best viewing angle
- Industrial electrical installation and troubleshooting
- Electronic testing and repair





Collapsing Screen

Specifications	Range	Max. Resolution	Basic Accuracy (%rdg+digits)
DC Voltage:	400mV to 400V	100µV	±(1.5% + 2d)
AC Voltage:	400mV to 400V	100µV	±(2.0% + 5d)
DC Current:	400mA	0.1mA	±(2.0% + 4d)
Resistance:	400 to 40MΩ	0.1Ω	±(2.0% + 2d)
Diode Test:	0 to 2V DC Test Current at 1mA		
Continuity Test:	Audible beep $<50\Omega$		
EF Test:	50 to 400VAC (50/60Hz)		
Battery Check:	1.5V Battery Check		
Power:	Two LR44 button batteries		
Dimensions:	0.75 x 4.6 x 2.8" (18 x 115 x 73mm)		



38109Mini Pocket MultiMeter

