

MiniTec® Digital MultiMeters

Rugged pocket design with 8 to 11 Functions

Includes Relative zero, Data Hold and Range Hold

- 4000 counts on large LCD with full function indication
- Measures AC/DC Voltage and Current, Resistance, Capacitance, Frequency and Temperature
- Temperature measurements to 1400°F (760°C)
- · Duty Cycle, Continuity and Diode test
- · Autoranging with manual range override
- 10A fuse protection
- Overload protection and indication
- · Auto power off saves battery life
- Includes protective rubber holster, two 1.5V AAA batteries and test leads



Test Leads included for easy measurements



MN25

Specifications	MN25	MN26T	Basic Accuracy (MN25/MN26T)	
	(Manual Ranging)	(Autoranging)		
Display Count	2000 count	4000 count		
DC Voltage	600V (0.1mV)	600V (0.1mV)	±0.5%	±1.0%
AC Voltage	600V (0.1V)	600V (0.1mV)	±1.5%	±1.5%
DC Current	10A (1μA)	10A (0.1μA)	±1.2%	±1.5%
AC Current	10A (1μA)	10A (0.1μA)	±1.8%	±1.8%
Resistance	$2M\Omega$ (0.1 Ω)	$40M\Omega$ (0.1 Ω)	±0.8%	±1.2%
Capacitance	_	200µF (0.001nF)	_	±3.5%
Frequency	_	10MHz (0.001Hz)	_	±1.5%
Temperature	_	0 to 1400°F (1°)	_	±3.0%
		0 to 760°C (1°)		
Duty Cycle	_	0.1% to 99.9% (0.	1%)	±1.2%
Diode/Continuity	Yes	Yes		
Warranty	1 year	1 year		
Dimensions/ Wt	4.8x2.4x1.6" (122x6	1x40mm)/ 9.17oz (2	60g)	

Ordering Information:

MN25Manual Ranging MiniTec® Digital MultiMeter

MN25-NIST Manual Ranging MiniTec® Digital MultiMeter w/ NIST Cert.

MN26TAuto Ranging MiniTec® Digital MultiMeter

MN26T-NIST .. Auto Ranging MiniTec® Digital MultiMeter w/ NIST Cert.

409992Vinyl Pouch Carrying Case







