

800A Clamp Meters

Full Featured Professional Clamp Meter With an ergonomically designed double molded housing for one hand operation and comfort.

EX700 Series Features:

- Models with AC/DC Current, AC/DC Voltage, Resistance, Frequency, Capacitance, Temperature, Diode, and Continuity
- True RMS Models (EX720, EX730)
- Peak function captures inrush currents and voltage transients
- Data Hold "freezes" data in display
- 1.2" (30mm) circular jaw opening for large cables (500MCM)
- Auto power off
- Complete with test leads, 9V battery, Type K bead wire probe and belt holster

Model EX710

AC Current


Model EX720

- AC Current
- True RMS
- Type K Temperature °F/°C switchable

Model EX730

- AC/DC Current
- True RMS
- Type K Temperature °F/°C switchable
- DC Zero





True RMS Clamp meter gives you accurate readings of nonsinusoidal waveforms

Complete with test leads, 9V battery, belt holster and Type K bead wire probe (-58 to 482°F/-50 to 250°C) (EX720/EX730 only).

EX700 series				
Specifications	EX710	EX720	EX730	Basic Accuracy
AC Current	0.01 to 800A	0.01 to 800A	0.01 to 800A	±2.8% (EX710) ±2.5% (EX720, EX730)
DC Current	—	—	✓ 0.1 to 800A	±2.5%
AC Voltage	0.1mV to 600V	0.1mV to 600V	0.1mV to 600V	±1.8% (EX710) ±1.5% (EX720, EX730)
DC Voltage	0.1mV to 600V	0.1mV to 600V	0.1mV to 600V	±1.5%
Resistance	0.1 to 40MΩ	0.1 to 40MΩ	0.1 to 40MΩ	±1.0%
Capacitance	0.001nF to 40,000µF	0.001nF to 40,000µF	0.001nF to 40,000µF	±3.0%
Frequency	0.001 to 4kHz	0.001 to 4kHz	0.001 to 4kHz	±1.5%
Temperature	—	✓-4 to 1400°F	✓-4 to 1400°F	±(3%rdg+9°F/5°C)
(Type K)			-20 to 760°C	-20 to 760°C
Continuity	Yes	Yes	Yes	
Inrush	Yes	Yes	Yes	
Diode	Yes	Yes	Yes	
Dimensions	9x3.1x1.9" (229x80x49mm) 9x3.1x1.9" (229x80x49mm) 9x3.1x1.9" (229x80x49mm)			
Weight	10.7 oz (303g)	10.7 oz (303g)	10.7 oz (303g)	

Ordering Information:

800A AC Clamp Meter 800A AC Clamp Meter with NIST Certificate

EX730......800A True RMS AC/DC Clamp Meter EX730-NIST800A True RMS AC/DC Clamp Meter w/NIST Certificate

www.extech.com