



Vane Thermo-Anemometer



Multifunction Air Velocity Meter

With built-in thermistor sensor for wide range temperature measurement

Features:

- Low friction ball bearing vane wheel (2.83"D) rotates freely in response to air flow
- 2% accuracy
- Super large (0.7") LCD display
- Data hold function allows user to freeze the displayed value in hard to see areas
- Ideal when reaching into an air duct or other HVAC applications
- Durable housing case and sensor is made of lightweight ABS plastic with a 39" (1m)
- Dimensions: 6.6 x 3.2 x 1.2" (168 x 81 x 30mm) meter; 2.83"D (72mm) vane; Weight: 12oz (340g)
- Complete with sensor, hard vinyl carrying case and 9V battery

| | EXTECH [®] | |
|-----------------------|---|--|
| 23 | 0 0.0 | |
| ANEMO | | |
| OMETER ANE IOBE | km/h ft/min (x10) m/s knots Temperature 0.4 to 30.0m/s 1.4 to 108.0km/h | |
| J | 80 to 5910t/min 0.8 to 58.3knots Thermo-Anemometer 451112 | |



Thermo-Anemometers Extech's Thermo-Anemometers with remote sensors are the most popular models for HVAC applications.

| Units | Range | Resolution | Basic Accuracy |
|-------------|--|------------|-------------------|
| ft/min | 80 to 5910ft/min | 10 | ±2% rdg±40 ft/min |
| m/s | 0.40 to 30.00m/s | 0.1 | ±2% rdg±0.20 m/s |
| km/hr | 1.4 to 108.0km/hr | 0.1 | ±2% rdg±0.6 km/h |
| Knots | 0.8 to 58.3 Knots | 0.1 | ±2% rdg±0.4knots |
| Temperature | 32 to 140°F (-0 to 60°C) | 0.1° | ±1.5°F/±0.8°C |
| Dimensions | 6.6 x 3.2 x 1.2" (168 x 81 x 30mm) meter 2.83"D (72mm) vane | | |
| Weight | 12oz (340g) | | |

Ordering Information:

451112Digital Vane Thermo-Anemometer 451112-NIST451112 with NIST Certificate

