

VESSEL MEGADORA® SERIES Global Standard Screwdrivers



ISO Specs.

EURO

Since these European Specification Screwdrivers () in this block are not manufactured as standard stock articles, VESSEL needs minimum quantity of 2,000 pieces per size when ordered by you.



EDP #	SIZE	Blade Width mm	Blade Thickness mm	Shank Length mm	Shank Diameter φ mm	Bolstered Shank A/F mm	Handle Diameter mm	O. A. L. mm
VESSEL MEGADORA STANDARD SCREWDRIVERS								
No.900 ⊕ Cross Recess / Standard Shank					Magnetic			
125705	P. 1x75	No. 1	75	5.5	—	30	175	175
125706	P. 2x100	No. 2	100	6.4	—	34	210	210
125707	P. 2x150	No. 2	150	6.4	—	34	260	260
125708	P. 3x150	No. 3	150	8.0	—	36	275	275
125710	P. 2x400	No. 2	400	6.4	—	34	510	510

EDP #	SIZE	Blade Width mm	Blade Thickness mm	Shank Length mm	Shank Diameter φ mm	Bolstered Shank A/F mm	Handle Diameter mm	O. A. L. mm
No.920 ⊕ Standard Shank STUBBY TYPE								
125753	P. 1x75	No. 1	25	6.4	—	36	75	75
125754	P. 2x25	No. 2	25	6.4	—	36	75	75
* 125755	1. 2x6. 5x25	6.5	1.2	25	6.4	—	36	75
* 125756	P. 1x30	No. 1	30	6.4	—	36	80	80
* 125757	P. 2x30	No. 2	30	6.4	—	36	80	80
* 125758	1. 2x6. 5x30	6.5	1.2	30	6.4	—	36	80

EDP #	SIZE	Blade Width mm	Blade Thickness mm	Shank Length mm	Shank Diameter φ mm	Bolstered Shank A/F mm	Handle Diameter mm	O. A. L. mm
No.910 ⊕ Cross Recess Standard Shank								
125741	P. 00x75	No. 00	75	3.0	—	21	153	153
125742	P. 0x75	No. 0	75	4.0	—	21	153	153

EDP #	SIZE	Blade Width mm	Blade Thickness mm	Shank Length mm	Shank Diameter φ mm	Bolstered Shank A/F mm	Handle Diameter mm	O. A. L. mm
* No.901 ⊖ Standard Shank								
122475	0.5x3x75	3	0.5	75	3.0	—	21	153
122472	0.8x4x75	4	0.8	75	4.0	—	21	153
122476	1x5. 5x75	5.5	1	75	5.5	—	30	175
122473	1x5. 5x100	5.5	1	100	5.5	—	30	200
122477	1. 2x6. 5x100	6.5	1.2	100	6.4	—	34	210
122478	1. 2x6. 5x150	6.5	1.2	150	6.4	—	34	260
122479	1. 2x8x125	8	1.2	125	8.0	—	36	250
122602	1. 2x8x150	8	1.2	150	8.0	—	36	275
122480	1. 2x8x200	8	1.2	150	8.0	—	36	325
122601	1. 2x6. 5x400	6.5	1.2	400	6.5	—	34	510
122603	1. 6x8x150	8	1.6	150	8.0	—	36	275
122604	1. 6x10x175	10	1.6	175	8.0	—	36	300
122482	1. 6x10x250	10	1.6	250	8.0	—	36	375

EDP #	SIZE	Blade Width mm	Blade Thickness mm	Shank Length mm	Shank Diameter φ mm	Bolstered Shank A/F mm	Handle Diameter mm	O. A. L. mm
* No.902 ⊖ Straight Shank								
122614	0.4x2. 5x50	2.5	0.4	50	3.0	—	21	128
122615	0.5x3x75	3.0	0.5	75	3.0	—	21	153
122616	0.5x3x100	3.0	0.5	100	3.0	—	21	178
122617	0.5x3x150	3.0	0.5	150	3.0	—	21	228
122618	0.6x3. 5x75	3.5	0.6	75	3.5	—	21	153
122619	0.6x3. 5x100	3.5	0.6	100	3.5	—	21	178
122620	0.8x4x75	4.0	0.8	75	4.0	—	21	153
122621	0.8x4x100	4.0	0.8	100	4.0	—	21	178
122607	0.8x4x150	4.0	0.8	150	4.0	—	21	228
122609	1x5. 5x100	5.5	1.0	100	5.5	—	30	200
122608	1x5. 5x150	5.5	1.0	150	5.5	—	30	250
122611	1x5. 5x200	5.5	1.0	200	5.5	—	30	300
122610	1. 2x6. 5x200	6.5	1.2	200	6.4	—	34	310
122612	1. 2x6. 5x250	6.5	1.2	250	6.4	—	34	360

EDP #	SIZE	Blade Width mm	Blade Thickness mm	Shank Length mm	Shank Diameter φ mm	Bolstered Shank A/F mm	Handle Diameter mm	O. A. L. mm
* No.903 ⊕ Pozipriv Standard Shank								
122624	PZ0x75	PZNo. 0	75	4.0	—	21	153	153
122625	PZ1x75	PZNo. 1	75	5.5	—	30	175	175
122627	PZ2x100	PZNo. 2	100	6.4	—	34	210	210
122628	PZ2x150	PZNo. 2	150	6.4	—	34	260	260
122630	PZ3x150	PZNo. 3	150	8.0	—	36	275	275
122622	PZ1x25	PZNo. 1	25	6.4	—	36	75	75
122623	PZ2x25	PZNo. 2	25	6.4	—	36	75	75

EDP #	SIZE	Blade Width mm	Blade Thickness mm	Shank Length mm	Shank Diameter φ mm	Bolstered Shank A/F mm	Handle Diameter mm	O. A. L. mm
VESSEL MEGADORA TANG-THRU SCREWDRIVERS								
No.930 ⊕ Cross Recess / Standard Shank					Magnetic			
125715	P. 1x75	No. 1	75	5.5	8	30	175	175
125720	P. 2x38	No. 2	38	6.4	10	34	151	151
125716	P. 2x100	No. 2	100	6.4	10	34	213	213
125717	P. 2x150	No. 2	150	6.4	10	34	263	263
125718	P. 3x150	No. 3	150	8.0	12	36	278	278

EDP #	SIZE	Blade Width mm	Blade Thickness mm	Shank Length mm	Shank Diameter φ mm	Bolstered Shank A/F mm	Handle Diameter mm	O. A. L. mm
* No.931 ⊖ Standard Shank								
122647	1x5. 5x75	5.5	1	75	5.5	8	30	176.5
122648	1. 2x6. 5x38	6.5	1.2	38	6.4	—	34	151
122649	1. 2x6. 5x100	6.5	1.2	100	6.4	10	34	213
122650	1. 2x8x150	8	1.2	150	8.0	12	36	263
122655	2x12x250	12	2.0	250	8.0	12	36	363

EDP #	SIZE	Blade Width mm	Blade Thickness mm	Shank Length mm	Shank Diameter φ mm	Bolstered Shank A/F mm	Handle Diameter mm	O. A. L. mm
* No.933 ⊕ Pozipriv Standard Shank								
122673	PZ1x75	PZNo. 1	75	5.5	8	30	176.5	176.5
122675	PZ2x100	PZNo. 2	100	6.4	10	34	213	213
122676	PZ2x150	PZNo. 2	150	6.4	10	34	263	263
122677	PZ3x150	PZNo. 3	150	8.0	12	36	278	278



Specs.

EDP #	SIZE	Blade Width mm	Blade Thickness mm	Shank Length mm	Shank Diameter φ mm	Bolstered Shank A/F mm	Handle Diameter mm	O. A. L. mm
No.940TX ● TORX Standard Shank								
125759	T5x80	T5	80	3.0	—	21	158	158
125760	T6x80	T6	80	3.0	—	21	158	158
125761	T7Hx80	T7H	80	3.0	—	21	158	158
125762	T8Hx80	T8H	80	3.0	—	21	158	158
125763	T9Hx80	T9H	80	3.0	—	21	158	158
125764	T10Hx80	T10H	80	3.0	—	21	158	158
125765	T15Hx80	T15H	80	4.0	—	21	158	158
125766	T20Hx120	T20H	120	4.0	—	21	198	198
125767	T25Hx120	T25H	120	5.5	—	30	220	220
125768	T27Hx120	T27H	120	5.5	—	30	220	220
125769	T30Hx120	T30H	120	6.4	—	34	230	230
125770	T40Hx120	T40H	120	7.0	—	34	230	230

EDP #	SIZE	Blade Width mm	Blade Thickness mm	Shank Length mm	Shank Diameter φ mm	Bolstered Shank A/F mm	Handle Diameter mm	O. A. L. mm
No.905 ● Hexagonal Standard Shank								
125771	A/F3x100	3.0	—	100	4.0	21	178	178
125772	A/F4x100	4.0	—	100	5.5	30	200	200
125773	A/F5x125	5.0	—	125	6.4	34	235	235
125774	A/F6x125	6.0	—	125	7.0	34	235	235
125775	A/F8x150	8.0	—	150	9.2	36	275	275

EDP #	SIZE	Blade Width mm	Blade Thickness mm	Shank Length mm	Shank Diameter φ mm	Bolstered Shank A/F mm	Handle Diameter mm	O. A. L. mm
No.906 ● Ultra-Ball Standard Shank								
125780	A/F1. 5x75	1.5	—	75	3.0	21	153	153
125781	A/F2x75	2.0	—	75	3.0	21	153	153
125782	A/F2. 5x100	2.5	—	100	3.0	21	178	178
125783	A/F3x100	3.0	—	100	4.0	21	178	178
125784	A/F4x100	4.0	—	100	5.5	30	200	200
125785	A/F5x125	5.0	—	125	6.4	34	235	235
125786	A/F6x125	6.0	—	125	7.0	34	235	235

EDP #	SIZE	Blade Width mm	Blade Thickness mm	Shank Length mm	Shank Diameter φ mm	Bolstered Shank A/F mm	Handle Diameter mm	O. A. L. mm
No.907 ○ Socket Nut Standard Shank								
125790	A/F5x100	5.0	8.0	20	100	5.0	34	210
125791	A/F5. 5x100	5.5	9.0	20	100	5.5	34	210
125792	A/F6x100	6.0	9.5	20	100	5.5	34	210
125793	A/F7x125	7.0	10.5	25	125	6.0	34	235
125794	A/F8x125	8.0	12.0	25	125	6.0	34	235
125795	A/F10x150	10.0	14.0	28	150	7.0	34	260
125796	A/F12x150	12.0	16.5	28	150	8.0	36	275
125797	A/F13x150	13.0	19.0	22	150	8.0	36	275

Min. QTY. Outer CTN: 60pcs.